

## Product Datasheet



## FOLAJET QD-WO

### White Opaque Film for Ink Jet Printers

A top coated white opaque polyester film for high resolution photographic poster prints, point of sale and pop up display panels. This film has excellent dimensional stability and flatness with good colour contrast reproduction even when using high levels of ink, reducing the possibility of material distortion.

The film is tear resistant and has high whiteness properties for a wider and more brilliant colour gamut. It offers excellent handling and lamination properties. Images dry quickly.



#### Characteristic

- Suitable for Thermal printers
- Suitable for Dye Ink
- Fast dry coating
- Good stiffness
- True colour
- Good flatness
- High resolution
- Tear resistant
- Fibre dust free
- No bleeding

#### Finish

- White opaque Surface

#### Specifications

- |                     |                   |
|---------------------|-------------------|
| • Coating frontside | For Ink Jet       |
| • Print side        | White opaque side |
| • Base material     | Polyester film    |

#### Compatibility

- Not compatible with oil and solvent based systems.
- Suitable for most Ink Jet Plotters using waterbased dye inks.

#### Handling

- A preconditioning period of 24 hours within the printing environment is recommended.
- Print side = matt white side
- Between 15-30°C and 30-70% r.h.
- Avoid fingerprints on printing side.
- Lamination: cold or heat lamination. To increase UV Protection, laminating is recommended.

#### Storage

- Store in a cool and dry place
- Shelf life min. 1 year after delivery (under recommended storage conditions).