

Product Datasheet



TACK JET P WO

Self adhering Ink Jet Film, matt white

White Opaque self-adhering indoor stickers for signage, labels, displays etc. The film does not have a sticky adhesive but clings to smooth clean surfaces like glass, plexi, wood or polished metal. Due to the special backing it can be repositioned without leaving any adhesive residue.

Please Note:

Not suitable for adhering onto soft PVC, copper or aluminium. This is due to the active sticking substances which may permanently damage the surface. Tack Jet P-WO is difficult to remove from some substrates such as PE or PP if the surfaces are chemically or corona treated.



Characteristic

- Suitable for Thermal printers
- Suitable for Piezo printers
- Suitable for Pigment Ink which offers improved light
- Suitable for Dye Ink
- Instant dry coating
- Improved water resistance
- Brilliant colour prints
- Can be repositioned without permanently bonding to surfaces
- Clings to smooth surfaces like glass, plexi etc.
- Excellent outstanding durability of the prints when using pigmented inks

Finish

- Matt white Surface

Specifications

- | | |
|---------------------|-----------------------------------|
| • Coating frontside | For Ink Jet |
| • Print side | Matt-White side |
| • Back side | Release paper, one side silicated |
| • Base material | Polypropylene |

Compatibility

- Suitable for most Ink Jet Plotters using dye- or pigmented inks.
- Not compatible with oil and solvent based systems.
- Please note:
Not suitable for adhering onto soft PVC, copper or aluminium. This is due to the active sticking substances which may permanently damage the surface. Tack Jet P-WO is difficult to remove from some substrates such as PE and PP if the surfaces are chemically or corona treated.

Handling

- A preconditioning period of 24 hours within the printing environment is recommended.
- Switch off automatic cutting device (damage to print heads and cutting knives).
- Print side = matt white side
- Between 15-30°C and 30-70% r.h.
- Printer Mode: photo quality, coated paper, o.e.
- Avoid fingerprints on printing side.
- Please follow the handling instructions supplied with this product as well as the machine manufacturers manual.

Storage

- Store in a cool and dry place
- Shelf life min. 1 year after delivery (under recommended storage conditions).

