

1-800-562-7760
(314) 447-2100
www.coastalbusiness.com

COASTAL[®]
BUSINESS SUPPLIES
Inc.

JetPro SofStretch Inkjet Transfer Paper

for **Light Colors**

Before you begin

For use in inkjet printers only. No lasers. Keep paper out of high humidity areas and away from moisture. Best if used on cotton and poly/cotton blend fabrics.

Soft & Stretchy!

Printing Instructions

1. Preparing Image

- Use normal print settings when preparing for print. No need to oversaturate with ink.
- Print design on the paper with the correct orientation. (MIRROR/REVERSE the image.) This can be done within the printer's property panel. For additional information, see your printer's instruction manual.
- Print the image on the blank side of the transfer paper. (side with no text)
- Check printer settings; single-sheet feeding is recommended.

2. Cut-out Design

- For best results trim the image before applying to garment.

Transferring Instructions

1. Preparing for Transfer:

Heat Press Application

- Prepare heat press at 350-375 degrees F.
- Place heat transfer paper with image facing down in desired position on fabric.
- Using the above recommended temperature, **apply firm pressure for 20-30 seconds.**
- Hot peel the transfer immediately after pressing. (Caution transfer will be hot.)

2. Hot Peel & Wear

- Peel the transfer immediately after pressing. (Caution, transfer will be hot.) For best results, stretch transferred area immediately after peeling. This product may also be cold peeled, but elasticity and durability decrease.

NOTE:

If your image is not transferring completely, increase your pressure and temperature. JetPro SofStretch requires heavy pressure and a high temperature to transfer successfully.

**Hand Iron is not recommended.
For best results, use heat press.**



Before Washing

Leave finish item for at least 24 hours before wash. Wash inside out in cold water. Dry at normal heat settings. Do not use bleach, fabric softener, or harsh detergents. Do not iron directly over transfer.

IMPORTANT: We thoroughly test each of our products on various substrates using different transfer equipment. However, it is impossible for us to duplicate all variables using all substrates and transfer equipment. Therefore, it is essential that you test the paper prior to production using your equipment, methods, and substrate material. Heat presses vary in accuracy. Conduct tests to determine the best time and temperature to use with your equipment. Please keep in mind that the Seller's and Manufacturer's maximum obligation shall be to replace any paper that has proven to be defective. Neither the Seller nor the Manufacturer shall be liable for injury, direct or consequential, arising out of the use of, or inability to use the paper.