

Laser 1 Opaque Laser Paper

APPLICATION INSTRUCTIONS

Laser Opaque Heat Transfer Paper for Color / Dark T-Shirts, SKU LASEROPAQUE



350° F



15-20 Seconds




Medium Pressure



Cold Peel

PRINTING INSTRUCTIONS

- For OKI 831TS, OKI 920WT and OKI 711WT: set the media type setting to Ultra Heavy 3
- For any other printer: Set the paper weight setting to Transparency or Label (usually the heaviest setting in the printer driver is most compatible)
- Print image on the blank, white side of the paper in the correct orientation: do NOT mirror/reverse the image.



- The paper should be fed into copier/printer with the short dimension first, ideally using a straight path bypass tray.
- We recommend single sheet feeding

Cut and Peel

- For best results trim away the unprinted paper around the image by hand or with a vinyl cutter.
- Gently peel the image off of the backing carrier like a sticker. Using an Xacto blade or a vinyl weeding tool is helpful to get easy separation of the layers.

APPLICATION INSTRUCTIONS

Heat Press

1. Prepare heat press at 350° F.
2. Do NOT pre-press the garment.

3. Place the printed image onto the fabric, facing up.
4. Cover the image with silicone paper. For a glossy finish, use Teflon cover.
5. Using above recommended temperature, apply MEDIUM pressure for 15-20 seconds. (Reduce time if using Dazzle-Trans with the application.)